



Minimum Cutbacks

ROLLER BLINDS

- Blockout fabrics 5mm
- Screen fabrics 10mm
- FRS: cannot cut back if fabric wrapped
- Bonded Pelmet: cannot be cut back or change fabric

VERTICAL BLINDS

- Slats: 150mm minimum
- Tracks: 5mm
- Pelmet: cannot be cut back

ALUMINIUM VENETIANS

Slimlines:

- 5mm in width
- Some cut backs in width may not be possible due to existing punch holes
This will need to be confirmed with the department

50mm aluminiums:

- 10mm in width
- Some cut backs in width may not be possible due to existing punch holes
This will need to be confirmed with the department

TIMBER VENETIANS

- 10mm in width
- Some cut backs in width may not be possible due to existing punch holes
This will need to be confirmed with the department
- Just for timbers, we cannot cut back headrail on control side, only slats

ROMAN BLINDS

Aluminium back batton:

- 10mm minimum in width
- 25mm minimum in drop

Side hems:

- Cannot cut back in the width any less than 80mm, however both side hems will be removed
- 25mm in drop

AWNINGS

- Canvas minimum cut back is 50mm
- and metal products is approx. 25mm minimum

ZIPSCREENS

- Zipscreen minimum cut back is 25mm
- and metal products is approx. 25mm minimum